

## Medium type Plastic conduit systems (750Nt)



### MEDISOL® AM Junction box / watertight with seals

#### Properties

Box raw material	PC blend
Temperature range	-25°C to +60°C
Electrical characteristics	With electrical insulated characteristics
Resistance to flame propagating	Non flame propagating
Number of entries	7
Kind of entries	Plug in seals
Ingress protection	IP 55
Number of base knock outs	4
Conduit alignment	Yes
Condensation opening	Yes
Flame retardant	650°C
Voltage	800V
Halogen free	No toxic or corrosive gases in case of fire
UV stability	Yes
Antimicrobial technology	Resist the growth of bacteria by up to 99% within 24 hours

\* Cover plate and plug in seals are made of PE

RAL 9003



#### Application Standards

EN 60670-22, EN 50642,  
ISO 22196, EU 98/8/EC (BPD)

#### Patents protected

1010513



Watertight due to their elastic and directly mounted cover plate.

MEDISOL AM adaptors, of different diameters, can be easily fastened in the openings after pushing out the plug in seals.



Type	Part number	A mm	B mm	C mm		
Ø16/20	3044016	67	38	21.6	10	280
Ø20/16	3044020	82	43	21.6	10	160
Ø25/32	3044025	101	51	35.1	5	100